


GLASS PASSIVATED BRIDGE RECTIFIERS

DB201 THRU DB207 50 to 1000 V 2.0A

FEATURES

- Glass passivated chip
- Plastic material has Underwriters Laboratory Flammability classification 94V-O
- High surge forward current capability
- Mounting Position: Any



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase , half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%.

Item	Symbol	Unit	Conditions	DB2						
				01	02	03	04	05	06	07
Repetitive Peak Reverse Voltage	V_{RRM}	V		50	100	200	400	600	800	1000
Average Rectified Output Current	I_o	A	60Hz sine wave, R-load , $T_a=25^\circ\text{C}$ On glass-epoxi substrate	2.0						
Surge(Non-repetitive)Forward Current	I_{FSM}	A	60HZ sine wave, 1 cycle, $T_j=25^\circ\text{C}$	60						
Current Squared Time	I^2t	A ² S	$1\text{ms} \leq t < 8.3\text{ms}$ $T_j=25^\circ\text{C}$, Rating of per diode	15						
Storage Temperature	T_{stg}	°C		-55 ~+150						
Junction Temperature	T_j	°C		-55 ~+150						
Dielectric Strength	V_{dis}	KV	Terminals to case , AC 1 minute	2.5						
Peak Forward Voltage	V_{FM}	V	$I_{FM}=17.5\text{A}$, Pulse measurement, Rating of per diode	1.1						
Peak Reverse Current	I_{RRM}	μ A	$V_{RM}=V_{RRM}$, Pulse measurement, Rating of per diode	10						
Thermal Resistance	R_{θ} J-A	°C/W	Between junction and ambient, Without heatsink	68						
	R_{θ} J-c		Between junction and case, With heatsink	15						

RATINGS AND CHARACTERISTIC CURVES

